



# HASA HI-TEMP SPA-GARD

## Material Safety Data Sheet

Emergency 24 Hour Telephone: CHEMTREC 800.424.9300

Corporate Headquarters: Hasa Inc.  
23119 Drayton Street  
Saugus, California 91350  
Telephone • 661.259.5848  
Fax • 661.259.1538



**HASA Hi-Temp SPA-GARD**  
Material Safety Data Sheet MSDS No. 402

### IDENTIFICATION OF PRODUCT

<b>Product Name:</b>	HASA HI-TEMP SPA-GARD
<b>Common Chemical Names:</b>	Dry chlorinating compound, granular chlorinating compound, DICHLOR, Sodium Dichloro-isocyanuric Acid, Dichloroisocyanuric Acid, Sodium Salt, Sodium Dichloro-s-triazinetrione
<b>Chemical Names of Ingredients:</b>	1,3-Dichloro-s-triazinetrione
<b>Chemical Family:</b>	Halogenated triazines
<b>CAS Registry Number:</b>	2893-78-9
<b>Empirical Formula:</b>	C <sub>3</sub> N <sub>3</sub> O <sub>3</sub> Cl <sub>2</sub> Na
<b>Molecular Weight:</b>	219

### PHYSICAL AND CHEMICAL PROPERTIES

<b>Vapor Pressure:</b>	Very small. Impossible to measure.	<b>Flash Point:</b>	Not Applicable.
<b>Weight/Gallon:</b>	Not Applicable.	<b>pH:</b>	6.8-7.2[1% solution]
<b>Density [liquid]:</b>	Not Applicable.	<b>Odor:</b>	Slight Chlorine
<b>Bulk Density:</b>	0.92-0.95 g/ml [57-59 lbs/ft <sup>3</sup> ]	<b>Boiling Point:</b>	Not Applicable.
<b>Melting Point:</b>	225-250°C	<b>Freezing Point:</b>	Not Applicable.
<b>Physical State:</b>	Crystalline solid.	<b>Color:</b>	White
<b>Solubility in Water:</b>	24.8 g/100 g H <sub>2</sub> O @ 26.8°C	<b>Stability:</b>	Stable

### PHYSICAL HAZARDS

<b>Potential for Fire:</b>	Addition of this product to a dispensing device containing other products or contamination with organic matter, moisture, or other chemicals may cause a violent reaction leading to fire or explosion.
<b>Potential for Explosion:</b>	Addition of this product to a dispensing device containing other products or contamination with organic matter, moisture, or other chemicals may cause a violent reaction leading to fire or explosion.
<b>Reactivity:</b>	Contamination with organic matter, moisture, or other chemicals may start a chemical reaction with the liberation of hazardous gases, including chlorine, nitrogen oxides, and cyanide, and possible generation of fire or explosion.
<b>Extinguishing Media:</b>	Water in excess.

<b>Fire Fighting Procedures:</b>	SCBA plus protective clothing.
----------------------------------	--------------------------------

HEALTH HAZARDS	
<b>Signs and Symptoms of Exposure:</b>	Eye and skin irritation.
<b>Medical Conditions Aggravated by Exposure:</b>	No data available.
<b>Oral [ingestion] LD<sub>50</sub>:</b>	No data available.
<b>Dermal [skin absorption] LD<sub>50</sub>:</b>	500 mg/24H [Mild]
<b>Inhalation [breathing] LC<sub>50</sub>:</b>	No data available.
<b>Eye Irritation:</b>	Severe. 10mg/34hr
<b>Skin Irritation:</b>	Mild. Not a skin sensitizer.
<b>OSHA PEL:</b>	None Established.
<b>ACGIH TLV/TWA:</b>	None Established.

POTENTIAL ROUTE [S] OF ENTRY	
<b>Inhalation [Breathing]:</b>	Dust may cause irritation to upper respiratory tract.
<b>Dermal [Skin]:</b>	Contact with broken skin may cause burning, blistering, and tissue destruction if not washed off immediately.
<b>Eyes:</b>	Irritating to the eyes. Corrosive. May cause permanent eye damage.
<b>Ingestion:</b>	Not anticipated.

CARCINOGENIC [CANCER POTENTIAL] INFORMATION	
<b>National Toxicological Program [NTP] <i>Sixth Annual Report on Carcinogens:</i></b>	Not listed.
<b>International Agency for Research on Cancer [IARC] <i>Monographs, V. 1-53, Supps. 1-8:</i></b>	Not listed.
<b>Listed by Federal OSHA as Carcinogens:</b>	Not listed.
<p><b>Safe Drinking Water and Toxic Enforcement Act of 1986 [Proposition 65, California only]:</b>            Small quantities – less than 100 ppm (parts per million) – of impurities, including bromates, may be found in all chlorinating products, including this product. Bromates are derived from bromides, which are present in sodium chloride (table salt) from which chlorine is manufactured. Additional small quantities of bromates may be generated during the disinfection process. Bromates are known by the State of California to cause cancer when administered by the oral (drinking or ingesting) route. Read and follow label directions and use care when handling or using this product. The US Environmental Protection Agency has established a maximum contaminant level (MCL) for bromates in drinking water at 10 ppb (parts per billion). Application of this product in accordance with label directions at use dilution will not exceed this level.</p> <p>This warning is provided pursuant to Proposition 65, the Safe Drinking Water and Toxic Enforcement act of 1986, Chapter 6.6 of the California Health and Safety Code, which requires the Governor of California to publish a list of chemicals “known to the state to cause cancer or reproductive toxicity.” This list is compiled in accordance with the procedures established under the proposition, and can be obtained on the internet from California’s Office of Environmental Health Hazard Assessment at <a href="http://www.oehha.ca.gov">http://www.oehha.ca.gov</a>. There are over 700 chemical substances on this list.</p>	

GENERAL PRECAUTIONS FOR SAFE USE AND HANDLING
Mix only with water. Do not mix with other chemicals. Use clean, dry utensils when mixing. Do not add this product to any dispensing device containing remnants of other products. A violent reaction or explosion may result when chemicals are mixed. Do not contaminate with moisture, other chemicals, or human wastes.

PERSONAL PROTECTION AND HYGIENE
Wear goggles or face shield and rubber gloves when handling. Avoid breathing dust. Remove and wash contaminated clothing before reuse. Wash hands after handling.

CLEAN-UP OF SPILLS	
Granules should be kept in tightly closed container when not in use in a cool, dry, ventilated area. Spilled materials should be picked up and placed in a dry container. If granules are contaminated by water or other chemicals, or human waste, place in a bucket with lots of clean water. Dissolved granules may be used on-site in pool or spa for disinfection or disposed of in an approved landfill. Small quantities of granules or solution made from granules may be discharged into a sanitary sewer. Granules must be disposed of in accordance with Federal, State, and/or local laws and regulations. Read the label for additional information. Contact HASA, Inc. for guidance.	

FIRST AID	
<b>Eye Contact:</b>	Flush with water. Remove contact lenses [if applicable]. Hold eyelids open. Continue flushing with water for 15 minutes. Get prompt medical attention.
<b>Skin Contact:</b>	Brush off any residue. Wash affected area with water for 15 minutes. If irritation persists, get medical attention.
<b>Ingestion [swallowing]:</b>	Feed bread soaked in milk followed by olive oil or other cooking oil. Call a physician immediately.
<b>Inhalation:</b>	Remove victim to fresh air. Call a physician.

FEDERAL/STATE LISTS/REGISTRATION/S/REPORTING REQUIREMENTS	
<b>CERCLA Hazardous Substance [Section 1010 [4], P.L. 96-510]:</b>	Not listed.
<b>Extremely Hazardous Substance [40 CFR 355, Appendix A]:</b>	Not listed.
<b>Pesticide Product 7 U.S.C. 136 et seq.:</b>	Registered as Pesticide Product by Federal EPA.
<b>Toxic Substance under TSCA:</b>	Not reported.
<b>Pesticide Product [various State Laws]:</b>	Registered as Pesticide Product.

MATERIAL CLASSIFICATION	
<b>OSHA Hazard Communication Standard, Department of Labor, Occupational Safety and Health Division, 29 CFR 1910.1200:</b>	Oxidizer

Hazardous Materials Transportation Regulations, Department of Transportation (Federal) 49 CFR 172.101	
<b>Material Class [Division]:</b>	5.1
<b>Packaging Group:</b>	II
<b>UN/NA Number:</b>	2468
<b>Label:</b>	Oxidizer 5.1
<b>Placard:</b>	Oxidizer 5.1
<b>Proper Shipping Name:</b>	Dichloroisocyanuric acid, sodium salt

<b>National Fire Protection Association NFPA 704 [1990]:</b>	2-0-1 OX
<b>NFPA 49:</b>	2-0-1 OX
<b>BOCA National Fire Prevention Code/National Building Code [1999 editions]:</b>	Oxidizer Class 2, Unstable [reactive] Class 1
<b>Standard Fire Prevention Code/Standard Building Code [1997 editions]:</b>	Oxidizer Class 2, Unstable [reactive] Class 1
<b>Uniform Fire Code/Uniform Building Code [1997 editions]:</b>	Oxidizer Class 2, Unstable [reactive] Class 1
<b>Uniform Fire Code Standards 79-3, Uniform Fire Code, V. II [1997 edition]:</b>	2-0-1-OX

**Please Note:** The information contained herein, while not guaranteed, was prepared by competent technical personnel and is true and accurate to the best of our knowledge and belief. NO WARRANTY OR GUARANTEE, expressed or implied, is made regarding the product performance, product stability, or as to any other condition of use, handling, transportation, and storage. Customer use, handling, transportation, and storage may involve additional safety and/or performance considerations. Our technical personnel will be happy to respond to questions regarding safe handling, storage, transportation and use procedures. The safe handling, storage, transportation and use procedures remain the sole responsibility of the customer. No suggestions for handling, storage, transportation or use are intended as or to be construed as recommendations which may infringe on any existing patents or violate any Federal, State, and/or local law and/or regulation, ordinance, standard, etc.. This Material Safety Data Sheet has been prepared by HASA, Inc. staff from test reports and other information available in the public domain.